



FlashBack®

ClickEffects

HD

PERIOD PLATES



WIPES,
DVE MOVES
& MUSIC BEDS

SPONSOR



MOVING
HEADSHOTS

Now, consolidate and streamline your replay capabilities with the Click Effects FlashBack system, the most versatile and affordable single or dual channel replay system available.

FEATURES & BENEFITS

- AVAILABLE IN SINGLE OR DUAL CHANNEL
- 20 + HOURS OF BROADCAST QUALITY VIDEO STORAGE
- CONTINUOUS RECORD WHILE PLAYING BACK CLIPS
- ASSEMBLE PLAYLISTS INSTANTLY, COMPLETE WITH AUDIO
- ASSIGN AND CUSTOMIZE CLIPS TO CATEGORIES
- CREATE AND EDIT HIGHLIGHT REELS
- VARIABLE SPEED, SLOMO CONTROL
- SEQUENCE SPONSOR TAGS, HEADSHOTS, SLATES AND TRANSITIONS WITH REPLAY CLIPS

Simplicity, Speed, Value.



ClickEffects®

Trusted by the best.



TECHNICAL SPECIFICATIONS

Video SD		Video HD	
Inputs	1 (analog/digital)	Inputs	1 (digital only)
Program Output	1 (analog/digital)	Program Output	1 (digital only)
Key output	1 (dedicated - digital only)	Key output	1 (dedicated - digital only)
Analog video I/O	1 component or Y/C or composite	Analog video I/O	N/A
Digital video I/O	SDI	Digital video I/O	HD-SDI
Digital bit rate	10 bit YUV 4:2:2	Digital bit rate	10 bit YUV 4:2:2
Genlock input	Analog black burst reference (bi-level)	Genlock input	Tri-level sync
Playback / Conversion		Playback / Conversion	
Video format	NTSC, PAL (4x3 or 16x9 support)	Video format	1080i @ 29.97 fps, 1080i @ 25fps, 720p @ 59.94 fps, 720p @ 50 fps
AVI Codecs	MPEG-2 I-Frame, DV25, DVCAM, DVCPRO50	AVI Codecs	MPEG-2 I-Frame, DVCPROHD
MOV Codecs	Sorenson, H.264, DV25, DVCAM, DVCPRO50, AVID™, Apple™ ProRes 422	MOV Codecs	DVCPROHD, AVID™ DNxHD ¹ , XDCAM ER 35, Apple™ ProRes 422 ¹
Audio		Audio	
Analog inputs	1 stereo pair (balanced XLR)	Analog inputs	N/A
Analog outputs	1 stereo pair (balanced XLR)	Analog outputs	N/A
Digital inputs	1 stereo pair AES/EBU (unbalanced)	Digital inputs	1 stereo pair AES/EBU (unbalanced)
Digital outputs	1 stereo pair AES/EBU (unbalanced)	Digital outputs	1 stereo pair AES/EBU (unbalanced)
Embedded SDI	1 stereo pair (Input and Output)	Embedded SDI	1 stereo pair (Input and Output)
Audio Format	48k sample rate, 16 bit, stereo, uncompressed	Audio Format	48k sample rate, 16 bit, stereo, uncompressed
Storage		Storage	
Storage Time	20 hours @ 50Mb/s (variable bit rate from 10Mb/s to 50Mb/s)	Storage Time	17 hours @ 125Mb/s (variable bit rate from 50Mb/s to 300Mb/s)
Capacity	500GB (standard) 1TB, 2TB, 4TB RAID (upgrade)	Capacity	1 TB (standard) 2TB, 4TB RAID (upgrade)
System		System	
Network Ports	(2) Gigabit Ethernet	Network Ports	(2) Gigabit Ethernet
COM Ports	(1) RS-232, (2) RS-422 (optional)	COM Ports	(1) RS-232, (2) RS-422
Power Supply	600 watt 120-250 VAC	Power Supply	Redundant 600 watt 120-250 VAC
Chassis	7" x 19" x 25" H-W-D 4RU	Chassis	7" x 19" x 25" H-W-D 4RU
Weight	60 lbs	Weight	60 lbs

¹ Video file conversion is required prior to playback